(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 22 January 2004 (22.01.2004)

PCT

(10) International Publication Number WO 2004/007969 A1

(51) International Patent Classification7: 29/00

F04C 19/00,

(21) International Application Number:

PCT/NO2003/000243

(22) International Filing Date:

9 July 2003 (09.07.2003)

(25) Filing Language:

Norwegian

(26) Publication Language:

English

(30) Priority Data: 20023393

12 July 2002 (12.07.2002) NO

- (71) Applicant (for all designated States except US): ROTO INTERNATIONAL AS [NO/NO]; P.O. Box 3 Holmlia, N-1201 Oslo (NO).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): HAGA, Johan [NO/NO]; Holteveien 21, N-1410 Kolbotn (NO).
- (74) Agent: ONSAGERS AS; P.O. Box 6963 St. Olavs plass, N-0130 Oslo (NO).


- (81) Designated States (national): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, F1 (utility model), F1, GB, GD, GB, GH, GM, HR, HU, ID, II, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: LIQUID RING COMPRESSOR



(57) Abstract: The invention relates to a liquid ring compressor and/or pump, comprising a rotating compressor casing (1), a shaft journal (10) eccentrically located relative to the compressor casing's axis of rotation, with a surrounding hearing (15). One or more compressor wheels (14) with at least one vane are disposed in the compressor casing with the inside of the compressor wheel (14) in abutment against and rotating around the bearing (15) and inlet and outlet ports for the fluid that has to be compressed. When the compressor casing is rotated, a liquid ring (20) is created against the inner wall of the rotating compressor casing (1), which liquid ring (20) together with the compressor wheel (14) forms compression chambers. The liquid ring compressor further comprises at least one magnetic element mounted in the compressor casing (1) adjacent to the compressor wheel (14), where when the compressor casing (1) is rotated, the magnetic element makes the free-running compressor wheel (14) rotate at the same rotational speed as the compressor casing (1).

WO 2004/00/969 A